

# 757 SAE 40

## Multipurpose

Multipurpose 757 SAE 40 formulated for private vehicle needs as well as commercial vehicles and heavy duty diesel. This lubricant can maximize engine performance with high rotation.



### Application:

private vehicle

commercial vehicle

heavy duty diesel.

0.8 Liter

1 Liter

4 Liter

## Lubricants for All Types of Machine

DELTALUBE MULTIPURPOSE is designed to support every kind of engine performances, starting from private vehicles, commercial vehicles, and heavy-duty diesel with its formulation maintaining engine quality with the use of an additive that can prevent rust and sludge. Multipurpose 75 works best for diesel and gasoline vehicle, or even industrial machine such as; marine, aviation, and printing that have a high rotation. Every base used by Deltalube has met and surpasses standard API Service SJ/CF-4.

### Advantages

- Works best for all type of private vehicle as well as commercial vehicles and heavy duty diesel.
- High-quality base oil, longer drain interval, more economical
- Optimizing protection with special additive that resists formation of rust, foam, carbon and sludge
- Maximizing engine power with special needs.
- Maintain engine cleanliness to reduce wear and provide comfort in driving.

### TEST RESULT

### FEEDBACKS / REVIEW

### DOWNLOADS

Characteristic	Unit	Result	Method
Color	–	Red	Visual
Density, @ 15°C	Kg/m <sup>3</sup>	882.9	ASTM D 1217
Kinematic Viscosity 40°C	cSt	143.8	ASTM D 445
Kinematic Viscosity 100°C	cSt	15.44	ASTM D 445
Viscosity Index	–	110	ASTM D 2270
Flash Point, COC	°C	>250	ASTM D 92
Pour Point	°C	-30	ASTM D 97
Copper Strip Corrosion	–	1a	ASTM D 130
Total Base Number	mgKOH/g	10.9	ASTM D 2896
Sulfated Ash Content	% wt	1.44	ASTM D 874
Foaming Tendency			
Seq I		0/0	
Seq II		0/0	
Seq III	ml	0/0	ASTM D 892